

□ □ □ □ □ □ □ □ □ □ □ □ *

Symbol:

A80G

□□□□□□□□□□.

260 g/m²

□□□□□□□□:

□□□□□□□□/□□□□□□ (65%
/35%)

Norm:

EN ISO 13688:2013.

□□□□□□□□ □□□□□

10

□□□□□□:

Kolorystyka:



0000000000 0000000000: 0000000000
 0000000000 0 00000 0 0000000 0000000 0 00000000,
 000000 0 0000000 000000 0000000,

WYMIARY			SIZE
□□□□	□□□□□	□□□□□	
164-170	084-088	076-080	44
164-170	088-092	080-084	46
164-170	092-096	084-088	24
164-170	096-100	088-092	25
170-176	096-100	088-092	50
170-176	092-096	084-088	48
170-176	100-104	092-096	26
170-176	104-108	096-100	27
170-176	108-112	100-104	28
170-176	112-116	104-108	29
176-182	092-096	084-088	98
176-182	104-108	096-100	54
176-182	116-120	108-112	30
176-182	100-104	092-096	52
176-182	120-124	112-116	31
176-182	124-128	116-120	32
182-188	108-112	100-104	56
182-188	112-116	104-108	58
182-188	096-100	088-092	102
188-194	100-104	092-096	106
188-194	116-120	108-112	60
188-194	120-124	112-116	62
188-194	104-108	096-100	110
194-200	124-128	116-120	64